

APR 16 2008

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

AMENDMENTS TO THE CLAIMS

1. (currently amended) A system ~~for reproducing audio signals~~, comprising:

an electronic entertainment system including at least one source of audio signals, the audio signals corresponding to at least one audio channel; and

a directed acoustic sound system including:

a modulated signal generator configured to generate an ultrasonic carrier signal modulated with at least one of the audio signals;

a driver amplifier configured to amplify the modulated ultrasonic carrier signal; and

at least one directional loudspeaker, the directional loudspeaker including at least one acoustic transducer configured to receive the modulated ultrasonic carrier signal amplified by the driver amplifier, and to project a sound beam representing the modulated ultrasonic carrier signal through a propagation medium along a pre-selected path to reproduce the at least one audio signal along at least a portion of the path.

2. (original) The system of claim 1 wherein the audio signals correspond to a plurality of audio channels, wherein the at least

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

one directional loudspeaker comprises a plurality of directional loudspeakers, and wherein a separate audio channel is provided for each directional loudspeaker.

3. (original) The system of claim 1 wherein the audio signals correspond to a plurality of audio channels, and wherein the modulated signal generator is configured to combine the plurality of audio channels and to generate the ultrasonic carrier signal modulated with the combined audio channels.

4. (previously presented) The system of claim 1 wherein the audio signals correspond to a plurality of audio channels, the plurality of audio channels being selected from the group consisting of a first audio channel corresponding to a first location in front of a user of the system, a second audio channel corresponding to a second location in back of the system user, a third audio channel corresponding to a third location to the left of the system user, and a fourth audio channel corresponding to a fourth location to the right of the system user, and wherein the modulated signal generator is configured to combine the plurality of audio channels, and to generate the ultrasonic carrier signal modulated with the combined audio channels.

-3-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

5. (previously presented) The system of claim 1:

wherein the directional loudspeaker is a parametric array;

wherein the system further includes a parametric array processor configured to control the parametric array, and at least one sensor configured to detect a distance from the directional loudspeaker to a user of the system or to detect a position of the user relative to the system; and

wherein the parametric array processor is configured to allow at least one parameter thereof to be adjusted based upon one or more of the detected distance from the directional loudspeaker to the user of the system, and the detected position of the user relative to the system.

6. (original) The system of claim 5 wherein the modulated signal generator is configured to generate an ultrasonic signal having characteristics based at least in part on the detected distance to the system user or the detected position of the system user.

7. (original) The system of claim 5 wherein the sensor comprises a device selected from the group consisting of an optical ranging

APR 16 2008

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

device, an acoustic ranging device, and an infrared ranging device.

8. (original) The system of claim 1 wherein the acoustic transducer is selected from the group consisting of a piezoelectric transducer, an electrostatic transducer, a PVDF film transducer, and an electrostrictive film transducer.

9. (original) The system of claim 1 further including a delay circuit configured to apply a relative phase shift across a plurality of frequencies of the modulated ultrasonic carrier signal to steer, focus, or shape the sound beam projected by the directional loudspeaker.

10. (currently amended) The system of claim 1:

wherein the electronic entertainment system is selected from the group consisting of a television, a radio, an audio tape player, a phonograph, a compact disk player, a digital video disk player, a laser disk player, a video game, a desktop computer, a laptop computer, and an MP3 system; and

wherein the directional loudspeaker is configured to direct the sound beam along the pre-selected path toward a user of the

APR 16 2008

008

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

electronic entertainment system, thereby preventing individuals other than the electronic entertainment system user from hearing sound produced by the electronic entertainment system.

11. (original) The system of claim 1 further including a second amplifier and at least one non-directional loudspeaker, the second amplifier being configured to amplify one or more audio signals corresponding to at least one of the audio channels and to drive at least one non-directional loudspeaker.

12. (original) The system of claim 11 wherein the modulated signal generator and the second amplifier are configured to receive the at least one audio channel in parallel.

13. (original) The system of claim 11 wherein the modulated signal generator is configured to receive the at least one audio channel and to provide a representation of the at least one audio channel to the second amplifier.

14. (original) The system of claim 11 wherein the modulated signal generator is configured to selectably generate the ultrasonic carrier signal modulated with the at least one of the

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

audio signals, and the second amplifier is configured to selectably amplify the one or more audio signals, thereby allowing only the directional loudspeaker, only the non-directional loudspeaker, or both the directional loudspeaker and the non-directional loudspeaker, to reproduce the audio signals.

15. (original) The system of claim 1 wherein the modulated signal generator includes an independent volume control.

16. (original) The system of claim 1 further including a remote signal receiver and a remote control device configured to generate remote signals in response to a user input, wherein the remote signal receiver is configured to receive the remote signals and generate control signals for controlling a system characteristic selected from the group consisting of a volume setting, a tone setting, and an output switch selection.

17. (original) The system of claim 16 wherein the remote control device is selected from the group consisting of an optical remote control device, an acoustic remote control device, an infrared remote control device, and a radio frequency remote control device.

-7-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0213

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

18. (original) The system of claim 1 further including a fan configured to cool the system.

19. (original) The system of claim 18 wherein the fan is activated automatically when a system temperature exceeds a predetermined level.

20. (previously presented) The system of claim 1 further including a swing-arm assembly configured to mount the directional loudspeaker to a ceiling, a floor, or a wall, and to direct of the projected sound beam along the pre-selected path.

21. (previously presented) The system of claim 1 further including a clamp assembly configured to mount the directional loudspeaker to a ceiling, a floor, or a wall, and to direct of the projected sound beam along the pre-selected path.

22. (currently amended) A method of reproducing audio signals, comprising the steps of:

providing at least one audio signal by at least one audio source included in an electronic entertainment system, the at

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

least one audio signal corresponding to at least one audio channel;

generating an ultrasonic carrier signal modulated with the at least one audio signal by a modulated signal generator included in a directed acoustic sound system;

amplifying the modulated ultrasonic carrier signal by a driver amplifier included in the directed acoustic sound system;

receiving, by at least one directional loudspeaker included in the directed acoustic sound system, the modulated ultrasonic carrier signal amplified by the driver amplifier ~~by at least one directional loudspeaker,~~ the at least one directional loudspeaker including at least one acoustic transducer; and

projecting, by the at least one directional loudspeaker, a sound beam representing the modulated ultrasonic carrier signal through a propagation medium along a pre-selected path to reproduce the at least one audio signal along at least a portion of the path ~~by the at least one directional loudspeaker.~~

23. (original) The method of claim 22 wherein the audio signals correspond to a plurality of audio channels, wherein the at least one directional loudspeaker comprises a plurality of directional



Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

loudspeakers, and further including the step of providing a separate audio channel for each directional loudspeaker.

24. (original) The method of claim 22 wherein the audio signals correspond to a plurality of audio channels, and further including the steps of combining the plurality of audio channels by the modulated signal generator, and generating the ultrasonic carrier signal modulated with the combined audio channels by the modulated signal generator.

25. (previously presented) The method of claim 22:

wherein the audio signals correspond to a plurality of audio channels, the plurality of audio channels being selected from the group consisting of a first audio channel corresponding to a first location in front of a user of the system, a second audio channel corresponding to a second location in back of the system user, a third audio channel corresponding to a third location to the left of the system user, and a fourth audio channel corresponding to a fourth location to the right of the system user; and

wherein the method further includes the steps of combining, by the modulated signal generator, the plurality of audio

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

channels, and generating the ultrasonic carrier signal modulated with the combined audio channels.

26. (previously presented) The method of claim 22:

wherein the directional loudspeaker is a parametric array controlled by a parametric array processor; and

wherein the method further includes the steps of:

detecting a distance from the directional loudspeaker to a user of the system or detecting a position of the user relative to the system by at least one sensor; and

adjusting at least one parameter of the parametric array processor based upon one or more of the detected distance from the directional loudspeaker to the user of the system, and the detected position of the user relative to the system.

27. (original) The method of claim 26 wherein the generating step includes generating an ultrasonic signal having characteristics based at least in part on the detected distance to the system user or the user position.

28. (original) The method of claim 26 wherein the sensor comprises a device selected from the group consisting of an

-11-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

APR 16 2008

Application No.: 10/697,208  
Filed: October 30, 2003  
TC Art Unit: 2615  
Confirmation No.: 2211

optical ranging device, an acoustic ranging device, and an infrared ranging device.

29. (original) The method of claim 22 wherein the acoustic transducer is selected from the group consisting of a piezoelectric transducer, an electrostatic transducer, a PVDF film transducer, and an electrostrictive film transducer.

30. (original) The method of claim 22 further including the step of applying a relative phase shift across a plurality of frequencies of the modulated ultrasonic carrier signal by a delay circuit, thereby steering, focusing, or shaping the sound beam projected by the directional loudspeaker.

31. (currently amended) The method of claim 22:

wherein the electronic entertainment system is selected from the group consisting of a television, a radio, an audio tape player, a phonograph, a compact disk player, a digital video disk player, a laser disk player, a video game, a desktop computer, a laptop computer, and an MP3 system; and

wherein the method further includes the step of directing the sound beam along the pre-selected path toward a user of the

-12-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LIEBOVICH LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

APR 16 2008

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

electronic entertainment system, thereby preventing individuals other than the electronic entertainment system user from hearing sound produced by the electronic entertainment system.

32. (original) The method of claim 22 further including the step of amplifying one or more audio signals corresponding to at least one of the audio channels by a second amplifier, and driving at least one non-directional loudspeaker by the second amplifier.

33. (original) The method of claim 32 further including the step of receiving the at least one audio channel in parallel by the modulated signal generator and the second amplifier.

34. (original) The method of claim 32 further including the steps of receiving the at least one audio channel by the modulated signal generator, and providing a representation of the at least one audio channel to the second amplifier by the modulated signal generator.

35. (original) The method of claim 32 further including the steps of selectably generating the ultrasonic carrier signal modulated with the at least one of the audio signals by the modulated signal

-13-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

generator, and selectably amplifying the one or more audio signals by the second amplifier, thereby allowing only the directional loudspeaker, only the non-directional loudspeaker, or both the directional loudspeaker and the non-directional loudspeaker, to reproduce the audio signals.

36. (currently amended) A ~~telephone system~~, comprising:

a telephone system including a receiver configured to receive information representative of at least one audio signal; and

a directed acoustic sound system including:

a modulated signal generator configured to generate an ultrasonic carrier signal modulated with the at least one audio signal;

a driver amplifier configured to amplify the modulated ultrasonic carrier signal; and

at least one directional loudspeaker, the directional loudspeaker including at least one acoustic transducer configured to receive the modulated ultrasonic carrier signal amplified by the driver amplifier, and to project a sound beam representing the modulated ultrasonic carrier signal through a propagation medium along a pre-selected path to reproduce the at least one audio signal along at least a portion of the path.

-14-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

37. (original) The system of claim 36 further including a second amplifier and at least one non-directional speaker, the second amplifier being configured to amplify at least one audio signal and to drive the non-directional loudspeaker.

38. (original) The system of claim 37 wherein the modulated signal generator and the second amplifier are configured to receive the at least one audio channel in parallel.

39. (original) The system of claim 37 wherein the modulated signal generator is configured to receive the at least one audio channel and to provide a representation of the at least one audio channel to the second amplifier.

40. (original) The system of claim 37 wherein the modulated signal generator is configured to selectably generate the ultrasonic carrier signal modulated with the at least one of the audio signals, and the second amplifier is configured to selectably amplify the one or more audio signals, thereby allowing only the directional loudspeaker, only the non-directional

-15-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

loudspeaker, or both the directional loudspeaker and the non-directional loudspeaker, to reproduce the audio signals.

41. (currently amended) A method of operating a telephone system, comprising the steps of:

receiving information representative of at least one audio signal by a receiver included in a telephone system;

generating an ultrasonic carrier signal modulated with the at least one audio signal by a modulated signal generator included in a directed acoustic sound system;

amplifying the modulated ultrasonic carrier signal by a driver amplifier included in the directed acoustic sound system;

receiving the modulated ultrasonic carrier signal amplified by the driver amplifier by at least one directional loudspeaker included in the directed acoustic sound system, the at least one directional loudspeaker including at least one acoustic transducer; and

projecting a sound beam representing the modulated ultrasonic carrier signal through a propagation medium along a pre-selected path by the directional loudspeaker, thereby reproducing the at least one audio signal along at least a portion of the path.

Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

42. (original) The method of claim 41 further including the steps of amplifying at least one audio signal by a second amplifier, and driving at least one non-directional loudspeaker by the second amplifier.

43. (original) The method of claim 42 further including the step of receiving the at least one audio signal in parallel by the modulated signal generator and the second amplifier.

44. (original) The method of claim 42 further including the steps of receiving the at least one audio channel by modulated signal generator, and providing a representation of the at least one audio channel to the second amplifier by the modulated signal generator.

45. (original) The method of claim 42 further including the steps of selectably generating the ultrasonic carrier signal modulated with the at least one of the audio signals by the modulated signal generator, and selectably amplifying the one or more audio signals by the second amplifier, thereby allowing only the directional loudspeaker, only the non-directional loudspeaker, or both the

-17-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313



Application No.: 10/697,208

Filed: October 30, 2003

TC Art Unit: 2615

Confirmation No.: 2211

directional loudspeaker and the non-directional loudspeaker, to reproduce the audio signals.

-18-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2290  
FAX. (617) 451-0313